Revised 12/2006

Unleaded. Unfailing. Unbeatable.™

*Use a roll crimp on 150-grain TSX FN bullets when loading cartridges intended for rifles with tubular magazines.

*The 130-grain TSX bullet has a spitzer ogive and is NOT suitable for use in tubular magazines. The COAL of cartridges loaded with this bullet is much longer than the SAAMI maximum, and is generally suitable for use only in single-shot firearms.

*The 130-grain TSX has a very short shank; we recommend using a factory crimp-style die to lightly crimp the case mouth to increase neck tension.

♦ Indicates most accurate load

.30-30 Winchester

Bullet Weight: 130 gr TSX BT
COAL: 2.720"
Case: Winchester
Case Trim Length: 2.030"
Primer: Fed GM210M
Barrel Length: 20"
Twist Rate: 1:12"
S.D. 0.196
B.C. 0.340

	Powder	Minimum Charge (grains)	Minimum Velocity (fps)	Maximum Charge (grains)	Maximum Velocity (fps)	Load Density (%)
♦	H4198	25.5	2239	27.0	2328	80
	Benchmark	30.5	2269	33.0	2453	91

Bullet Weight: 150 gr
Bullet Style: TSX FN
COAL: 2.470"
Case: Winchester
Case Trim Length: 2.030"
Primer: Fed GM210M
Barrel Length: 20"
Twist Rate: 1:12"
S.D. 0.226
B.C. 0.184

	Powder	Minimum Charge (grains)	Minimum Velocity (fps)	Maximum Charge (grains)	Maximum Velocity (fps)	Load Density (%)
	Win 748	31.5	2039	34.0	2168	96
♦	TAC	30.5	2006	32.0	2096	90