

# 338 Rem Ultra Mag

Case: Remington

Primer: Remington 9 1/2M

Case Trim: 2.750"

Barrel Length: 24"

Twist Rate: 1:10"

Barrel: Bartlein

Maximum Loads Should Be Used With Caution - Always Start With Minimum Loads.

*\*Recommended Load*

*° Compressed Load*

## 338 Rem Ultra Mag



185-grain TSX BT  
Sectional Density .231  
Ballistic Coefficient .352  
C.O.A.L 3.575"

Suggested Bullet Use



185-grain TTSX BT  
Sectional Density .231  
Ballistic Coefficient .432  
C.O.A.L 3.600"

Suggested Bullet Use



Powder	Minimum		Maximum	
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)
Vit N560	88.0	3121	96.0	3336
*MagPro	95.0	3194	100.0	3311
RL 22	89.0	3157	96.5	3379
IMR 7828ssc	88.0	3090	95.5	3302
H1000	94.5	3095	102.5 <sup>c</sup>	3292
Magnum	97.0	3147	104.0	3363



210-grain TSX BT  
Sectional Density .263  
Ballistic Coefficient .404  
C.O.A.L 3.575"

Suggested Bullet Use



210-grain TTSX BT  
Sectional Density .263  
Ballistic Coefficient .482  
C.O.A.L 3.600"

Suggested Bullet Use



Powder	Minimum		Maximum	
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)
RL 22	84.5	2982	92.5	3189
*IMR 7828ssc	84.5	2913	92.0	3117
H1000	90.0	2912	98.0 <sup>c</sup>	3109
Magnum	91.5	2973	99.0	3176
RL 25	87.5	3025	95.5	3185
Retumbo	88.5	2954	96.5 <sup>c</sup>	3135

Maximum Loads Should Be Used With Caution - Always Start With Minimum Loads.

\*Recommended Load

<sup>c</sup> Compressed Load

## 338 Rem Ultra Mag



225-grain TSX FB  
Sectional Density .281  
Ballistic Coefficient .386  
C.O.A.L 3.575"

Suggested Bullet Use



Powder	Minimum		Maximum	
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)
RL 22	81.0	2864	89.5	3057
IMR 7828ssc	80.0	2772	89.0	2995
H1000	87.5	2799	95.0 <sup>c</sup>	2985
Magnum	90.0	2870	97.5	3066
*Retumbo	84.5	2833	93.0 <sup>c</sup>	3017



225-grain TTSX BT  
Sectional Density .281  
Ballistic Coefficient .514  
C.O.A.L 3.600"

Suggested Bullet Use



250-grain TSX FB  
Sectional Density .313  
Ballistic Coefficient .425  
C.O.A.L 3.575"

Suggested Bullet Use



Powder	Minimum		Maximum	
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)
RL 22	80.5	2701	89.0	2906
IMR 7828ssc	78.5	2611	86.5	2834
H1000	84.5	2648	92.0 <sup>c</sup>	2833
Magnum	87.5	2731	95.0	2915
*Retumbo	83.5	2699	91.0 <sup>c</sup>	2872

Maximum Loads Should Be Used With Caution - Always Start With Minimum Loads.

\*Recommended Load

<sup>c</sup> Compressed Load

## 338 Rem Ultra Mag



265-grain LRX BT  
Sectional Density .331  
Ballistic Coefficient .575  
C.O.A.L 3.600"

Suggested Bullet Use



Powder	Minimum		Maximum	
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)
Hybrid 100v	69.3	2541	77.0	2763
H4831sc	76.2	2550	84.7	2765
IMR 4831	74.0	2552	82.2	2774
RL 22	69.9	2485	77.6	2711
*IMR 7828ssc	76.5	2521	85.0	2780
Magnum	83.6	2579	92.9 <sup>c</sup>	2836



280-grain LRX BT  
Sectional Density .350  
Ballistic Coefficient .667  
C.O.A.L 3.600"

Suggested Bullet Use



Powder	Minimum		Maximum	
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)
Hybrid 100v	67.1	2431	74.6	2640
H4831sc	71.7	2400	79.7	2611
IMR 4831	70.2	2413	78.0	2611
RL 22	67.3	2376	74.8	2571
IMR 7828ssc	74.1	2452	82.4	2674
*Magnum	81.4	2480	90.4 <sup>c</sup>	2728

Maximum Loads Should Be Used With Caution - Always Start With Minimum Loads.

\*Recommended Load

<sup>c</sup> Compressed Load

# 338 Rem Ultra Mag



285-grain TSX BT  
 Sectional Density .356  
 Ballistic Coefficient .585  
 C.O.A.L 3.600"

Suggested Bullet Use



Powder	Minimum		Maximum	
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)
Hybrid 100v	67.1	2422	74.6	2626
H4831sc	71.2	2385	79.1	2597
IMR 4831	67.3	2385	74.8	2564
RL 22	66.3	2349	73.6	2561
IMR 7828ssc	71.3	2411	79.2	2612
*Magnum	77.1	2417	85.7	2649

Maximum Loads Should Be Used With Caution - Always Start With Minimum Loads.

\*Recommended Load

° Compressed Load