



\*A slight crimp was used to ensure the bullet neck tension was strong enough to keep the bullet from moving.

◆ Indicates most accurate load

**.458 Winchester Magnum**

**Bullet Weight:** 450 gr                      **Case Trim Length:** 2.490"                      **S.D.**            0.306  
**Bullet Style:** TSX FB                                      **Primer:** Fed GM215M                      **B.C.**            0.369  
**COAL:** 3.340"                                      **Barrel Length:** 24"  
**Case:** W-W    **Twist Rate:** 1:14"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
H4198	49.0	1874	57.0	2070	94
XMR 2015	61.0	2033	66.0	2176	104
RL 7	57.0	2007	61.5	2146	100
X-Terminator	64.0	2024	70.0	2213	103
H335	68.5	2076	72.5	2232	101
◆ TAC	68.5	2109	73.5	2242	105

**Bullet Weight:** 450 gr                      **Case Trim Length:** 2.490"                      **S.D.**            0.306  
**Bullet Style:** Banded Solid                                      **Primer:** Fed GM215M                      **B.C.**            0.362  
**COAL:** 3.310"                                      **Barrel Length:** 24"  
**Case:** W-W    **Twist Rate:** 1:14"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
H4198	55.0	2065	61.5	2210	95
XMR 2015	63.0	2137	69.5	2290	102
RL 7	58.0	2080	64.5	2245	98
◆ X-Terminator	68.0	2173	74.0	2328	101
H335	73.0	2229	79.0	2385	102
TAC	73.0	2234	79.0	2379	105

## .458 Winchester Magnum

**Bullet Weight:** 500 gr  
**Bullet Style:** TSX FB  
**COAL:** 3.340"  
**Case:** W-W

**Case Trim Length:** 2.490"  
**Primer:** Fed GM215M  
**Barrel Length:** 24"  
**Twist Rate:** 1:14"

**S.D.** 0.341  
**B.C.** 0.412

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
H4198	48.0	1747	52.5	1884	95
♦ XMR 2015	54.5	1804	58.5	1930	101
RL 7	51.0	1775	55.0	1921	98
X-Terminator	58.0	1843	62.5	1985	101
H335	61.0	1851	65.0	2000	99
TAC	62.5	1915	67.0	2040	105

**Bullet Weight:** 500 gr  
**Bullet Style:** Banded Solid  
**COAL:** 3.310"  
**Case:** W-W

**Case Trim Length:** 2.490"  
**Primer:** Fed GM215M  
**Barrel Length:** 24"  
**Twist Rate:** 1:14"

**S.D.** 0.341  
**B.C.** 0.394

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
♦ H4198	49.0	1857	55.5	1999	93
XMR 2015	58.0	1959	63.0	2077	100
RL 7	54.0	1919	59.5	2067	98
X-Terminator	62.0	1979	67.5	2124	100
H335	66.5	2036	72.0	2183	102
TAC	67.0	2062	72.5	2194	105