



*This load data was test fired up to the SAAMI maximum average pressure (MAP) of 51,000 psi.

◆ Indicates most accurate loads

6.5 x 55 Swedish Mauser

Bullet Weight: 110 gr **Case Trim Length:** 2.155" **S.D.** 0.225
Bullet Style: Banded Spitzer Solid **Primer:** Fed GM210M **B.C.** 0.452
COAL: 2.980" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:8"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
IMR 4831	43.0	2668	47.0	2905	98
XMR 3100	43.5	2681	47.5	2899	100
Mag Pro	49.0	2768	54.5	3007	100
VIT N165	43.0	2715	48.0	2920	96
◆ RL 22	45.5	2737	49.0	2931	98
IMR 7828SSC	45.0	2635	49.0	2866	95

Bullet Weight: 120 gr **Case Trim Length:** 2.155" **S.D.** 0.246
Bullet Style: TSX BT **Primer:** Fed GM210M **B.C.** 0.381
COAL: 2.950" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:8"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
IMR 4831	40.5	2519	44.5	2744	93
XMR 3100	41.5	2541	45.5	2751	96
Mag Pro	46.0	2568	51.0	2814	93
◆ RL 22	41.0	2530	46.0	2762	92
IMR 7828SSC	43.0	2498	47.0	2718	91
H1000	45.5	2485	50.0	2707	100

Bullet Weight: 130 gr **Case Trim Length:** 2.155" **S.D.** 0.266
Bullet Style: TSX FB **Primer:** Fed GM210M **B.C.** 0.365
COAL: 2.950" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:8"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
IMR 4831	39.0	2349	43.0	2568	92
XMR 3100	39.5	2376	43.5	2574	94
Mag Pro	44.0	2443	49.0	2655	92
◆ RL 22	39.0	2399	44.0	2594	91
IMR 7828SSC	41.0	2365	45.0	2584	90
H1000	43.5	2370	47.5	2557	98