

6.5 Grendel

Case: Hornady


Primer: Federal 205

Case Trim: 1.506"

Barrel Length: 24"

Twist Rate: 1:8"

Barrel: Satern



Maximum Loads Should Be Used With Caution - Always Start With Minimum Loads.

**Recommended Powder*

[°] Compressed Load

6.5 Grendel



100-grain TTSX BT / TAC-TX BT
Sectional Density .205
Ballistic Coefficient .359
C.O.A.L 2.260"

Suggested Bullet Use



Powder	Minimum		Maximum	
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)
PowerPro 1200-R	25.5	2612	28.4	2837
Benchmark	26.2	2565	29.1 ^c	2817
X-Terminator	26.4	2574	29.3 ^c	2812
IMR 8208 XBR	26.5	2618	29.5 ^c	2855
A-2460	27.3	2683	30.3 ^c	2901
H335	27.4	2621	30.4 ^c	2865
*RL 15	26.8	2602	29.7 ^c	2846



120-grain TSX BT / TAC-X BT
Sectional Density .246
Ballistic Coefficient .381
C.O.A.L 2.260"

Suggested Bullet Use



120-grain TTSX BT / TAC-TX BT
Sectional Density .246
Ballistic Coefficient .412
C.O.A.L 2.260"

Suggested Bullet Use



Powder	Minimum		Maximum	
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)
PowerPro 1200-R	23.5	2262	26.1	2480
Benchmark	24.3	2241	27.0 ^c	2483
X-Terminator	24.6	2265	27.3 ^c	2489
RL 10X	21.4	2154	23.8	2378
IMR 8208 XBR	24.4	2264	27.1 ^c	2498
H335	25.2	2279	28.0 ^c	2519
*RL 15	24.3	2279	27.0 ^c	2511

Maximum Loads Should Be Used With Caution - Always Start With Minimum Loads.

*Recommended Powder

^c Compressed Load

6.5 Grendel



140-grain Match Burner

Sectional Density .287

Ballistic Coefficient .586

C.O.A.L 2.240"

Suggested Bullet Use



Powder	Minimum		Maximum	
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)
PowerPro 1200-R	23.2	2207	25.8	2411
Benchmark	23.4	2181	26.0	2386
RL 10X	21.7	2164	24.1	2347
*IMR 8208 XBR	24.1	2203	26.8 ^c	2414
H335	24.9	2222	27.6 ^c	2451
TAC	25.4	2204	28.3 ^c	2445

Maximum Loads Should Be Used With Caution - Always Start With Minimum Loads.

**Recommended Powder*

^c Compressed Load