



*A 1:9" or faster twist is recommended for the 175-grain TSX bullet.

◆ Indicates most accurate load

7mm Remington Ultra Magnum

Bullet Weight: 120 gr **Case Trim Length:** 2.840" **S.D.** 0.213
Bullet Style: TSX BT **Primer:** Fed GM215M **B.C.** 0.349
COAL: 3.575" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9.5"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
Hunter	79.0	3365	84.0	3512	76
RL 19	85.5	3378	92.0	3604	90
IMR 4831	84.5	3380	89.0	3609	89
XMR 3100	86.0	3407	91.0	3615	92
H4831SC	87.0	3340	93.0	3562	90
MagPro	90.0	3352	95.5	3573	84
RL 22	88.0	3397	94.0	3673	91
◆ IMR 7828SSC	89.5	3362	93.5	3612	87
AA 8700	104.5	3313	110.5	3543	98
H1000	93.0	3351	97.5	3558	94

Bullet Weight: 140 gr **Case Trim Length:** 2.840" **S.D.** 0.248
Bullet Style: Banded Spitzer Solid **Primer:** Fed GM215M **B.C.** 0.464
COAL: 3.590" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9.5"

Bullet Weight: 140 gr **Case Trim Length:** 2.840" **S.D.** 0.248
Bullet Style: TSX BT **Primer:** Fed GM215M **B.C.** 0.394
COAL: 3.575" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9.5"

Bullet Weight: 140 gr **Case Trim Length:** 2.840" **S.D.** 0.248
Bullet Style: MRX BT **Primer:** Fed GM215M **B.C.** 0.406
COAL: 3.580" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9.5"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
XMR 3100	81.5	3138	87.0	3346	90
◆ H4831SC	83.5	3136	89.0	3335	88
MagPro	84.0	3097	92.0	3319	82
RL 22	85.0	3191	89.0	3411	88
IMR 7828SSC	85.0	3155	90.5	3371	86
AA 8700	98.5	3104	105.0	3344	95
H1000	89.0	3140	94.0	3339	93
Magnum	90.0	3189	96.0	3381	87
RL 25	87.5	3175	93.5	3427	92
US869	101.5	3207	106.5	3416	95

7mm Remington Ultra Magnum

Bullet Weight: 150 gr **Case Trim Length:** 2.840" **S.D.** 0.266
Bullet Style: TSX BT **Primer:** Fed GM215M **B.C.** 0.408
COAL: 3.575" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9.5"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
XMR 3100	79.0	3009	84.0	3212	88
H4831SC	77.0	2977	84.5	3188	84
MagPro	80.5	2998	88.0	3194	80
RL 22	80.0	3043	87.5	3290	87
♦ IMR 7828SSC	81.0	2999	88.0	3249	85
AA 8700	98.0	3066	103.5	3265	95
H1000	85.5	3005	91.5	3238	91
Magnum	88.0	3088	94.5	3297	87
RL 25	83.0	3054	91.0	3306	90
US869	99.0	3119	106.0	3347	95

Bullet Weight: 160 gr **Case Trim Length:** 2.840" **S.D.** 0.283
Bullet Style: TSX FB **Primer:** Fed GM215M **B.C.** 0.392
COAL: 3.575" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9.5"

Bullet Weight: 160 gr **Case Trim Length:** 2.840" **S.D.** 0.283
Bullet Style: MRX BT **Primer:** Fed GM215M **B.C.** 0.439
COAL: 3.580" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9.5"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
XMR 3100	75.0	2862	82.0	3085	87
H4831SC	74.5	2834	81.5	3056	82
MagPro	77.0	2830	84.0	3049	77
RL 22	76.0	2899	82.0	3086	83
♦ IMR 7828SSC	77.0	2858	83.5	3070	82
AA 8700	96.0	2964	101.0	3155	93
H1000	80.0	2843	87.5	3062	88
Magnum	86.0	2983	92.0	3175	86
RL 25	78.0	2899	86.0	3098	86
US869	96.5	3015	102.5	3211	93

Bullet Weight: 175 gr **Case Trim Length:** 2.840" **S.D.** 0.310
Bullet Style: TSX FB **Primer:** Fed GM215M **B.C.** 0.417
COAL: 3.575" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:9.5"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
H4831SC	71.0	2699	78.5	2920	81
MagPro	74.0	2679	81.0	2919	76
RL 22	73.0	2748	80.0	2960	82
IMR 7828SSC	75.0	2746	81.5	2961	81
AA 8700	93.5	2851	99.0	3072	93
H1000	78.0	2759	84.0	2943	87
Magnum	81.0	2826	89.0	3058	84
RL 25	76.0	2765	84.0	2985	86
US869	93.0	2891	99.0	3091	92
♦ H50BMG	87.5	2832	95.5	3024	99