



*Recommend crimping the case mouth into the front cannellure groove.

*The CIP maximum COAL is 3.468" for this cartridge. The Barnes 535-gr Banded Solid (#51053) is designed specifically for this cartridge and will fit magazines designed to CIP specs.

*Barnes' 570-grain TSX and 570-grain Banded Solid bullets are designed for the .500 NE. Their cannellure positions require a COAL longer than CIP specs for the .500 Jeffery.

*Check your magazine length, and try feeding with a dummy round before loading 570-grain bullets to the listed COAL.

◆ Indicates most accurate loads

.500 Jeffery

Bullet Weight: 535 gr	Case Trim Length: 2.740"	S.D.	0.294
Bullet Style: Banded Solid	Primer: Fed GM215M	B.C.	0.215
COAL: 3.440"	Barrel Length: 26"		
Case: Jamison	Twist Rate: 1:20"		

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ IMR 4895	99.0	2198	107.0	2394	94
Varget	101.0	2247	108.0	2407	94
RL 15	102.5	2260	110.5	2427	96
VIT N150	106.0	2291	114.0	2440	99

Bullet Weight: 570 gr	Case Trim Length: 2.740"	S.D.	0.314
Bullet Style: Banded Solid	Primer: Fed GM215M	B.C.	0.243
COAL: 3.485"	Barrel Length: 26"		
Case: Jamison	Twist Rate: 1:20"		

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
IMR 4895	98.0	2183	106.0	2335	95
Varget	99.0	2169	107.0	2350	96
◆ RL 15	101.0	2199	109.0	2349	98
VIT N150	104.0	2214	112.0	2381	100

.500 Jeffery

Bullet Weight: 570 gr
Bullet Style: TSX FB
COAL: 3.505"
Case: Jamison

Case Trim Length: 2.740"
Primer: Fed GM215M
Barrel Length: 26"
Twist Rate: 1:20"

S.D. 0.314
B.C. 0.369

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
♦ IMR 4895	93.0	2056	101.0	2246	96
Varget	94.5	2076	101.5	2246	96
RL 15	97.0	2119	105.0	2286	100
VIT N150	99.0	2131	107.0	2295	101
