

Revised 7/2006



*Recommend crimping case mouth into front cannelure groove.

◆ Indicates most accurate load

.505 Gibbs

Bullet Weight: 525 gr **Case Trim Length:** 3.140" **S.D.** 0.294
Bullet Style: TSX FB **Primer:** Federal GM215M **B.C.** 0.320
COAL: 3.830" **Barrel Length:** 23."
Case: Jamison **Twist Rate:** 1:16"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
MagPro	131.0	2014	141.0	2194	94
RL 22	125.5	2043	133.0	2223	98
◆ Win WXR	123.5	1999	131.0	2194	96
IMR 7828SSC	120.0	1945	130.0	2155	92
H1000	132.5	2053	139.0	2197	102
RL 25	136.0	2125	144.0	2287	105

Bullet Weight: 525 gr **Case Trim Length:** 3.140" **S.D.** 0.294
Bullet Style: Banded Solid **Primer:** Federal GM215M **B.C.** 0.226
COAL: 3.830" **Barrel Length:** 23."
Case: Jamison **Twist Rate:** 1:16"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
MagPro	142.5	2193	152.5	2359	102
RL 22	128.0	2084	138.0	2295	101
Win WXR	127.5	2079	136.0	2245	100
IMR 7828SSC	127.0	2062	135.5	2230	96
H1000	137.0	2094	144.5	2265	106
◆ RL 25	141.0	2165	150.5	2348	110
