



*This cartridge will not stabilize 53-, 62-, and 70-grain TSX bullets fired in 1:14" twist barrels. It produces good stability with 36-grain Varmint Grenade bullets.

*A 1:12" or faster twist is required to stabilize the 45-grain Banded Spitzer; a 1:14" rifling twist will not stabilize this bullet.

◆ Indicates most accurate load

222 Remington

Bullet Weight: 30 gr **Case Trim Length:** 1.690" **S.D.** 0.085
Bullet Style: VG FB **Primer:** Fed 205 **B.C.** 0.101
COAL: 2.040" **Barrel Length:** 24"
Case: W-W **Twist Rate:** 1:14"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
H4198	19.8	3397	21.8	3864	93
IMR 4198	19.0	3378	21.0	3796	95
X-Terminator	24.2	3589	26.2	3775	99
RL 10X	22.2	3582	24.2	3865	100
◆ AA 2460	25.0	3644	27.0	3815	101
H335	24.0	3505	26.0	3741	93

Bullet Weight: 36 gr **Case Trim Length:** 1.690" **S.D.** 0.102
Bullet Style: Varmint Grenade **Primer:** WSR **B.C.** 0.149
COAL: 2.100" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:14"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
IMR 4198	18.0	3132	20.0	3462	94
X-Terminator	22.5	3300	24.5	3530	96
◆ Win 748	25.0	3350	27.5	3524	104
RL 10X	21.0	3236	23.0	3591	98
H335	23.0	3277	25.0	3502	93
TAC	24.0	3362	26.0	3555	99

Bullet Weight: 45 gr **Case Trim Length:** 1.690" **S.D.** 0.128
Bullet Style: Banded Spitzer **Primer:** WSR **B.C.** 0.195
COAL: 2.130" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:14"

Bullet Weight: 45 gr **Case Trim Length:** 1.690" **S.D.** 0.128
Bullet Style: TSX FB **Primer:** WSR **B.C.** 0.188
COAL: 2.130" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:14"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
IMR 4198	17.5	2912	19.5	3223	91
X-Terminator	21.5	3054	23.5	3261	91
◆ Win 748	24.0	3152	26.0	3312	98
RL 10X	20.5	3036	22.5	3353	96
H335	22.0	2952	24.0	3281	88

Bullet Weight: 50 gr
Bullet Style: TSX FB
COAL: 2.120"
Case: W-W

Case Trim Length: 1.690"
Primer: Fed 205
Barrel Length: 24"
Twist Rate: 1:14"

S.D. 0.142
B.C. 0.197

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
IMR 3031	20.2	2705	22.2	3028	101
♦ H322	19.6	2758	21.6	3052	92
RL 10X	18.6	2766	20.6	3051	89
AA 2460	21.0	2853	23.0	3096	89
H335	20.6	2774	22.6	3030	84
TAC	22.4	2863	24.4	3114	93

Bullet Weight: 53 gr
Bullet Style: TSX FB
COAL: 2.130"
Case: R-P

Case Trim Length: 1.690"
Primer: WSR
Barrel Length: 24"
Twist Rate: 1:14"

S.D. 0.151
B.C. 0.204

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
X-Terminator	20.5	2801	22.5	3041	91
Win 748	22.5	2859	24.5	3088	96
RL 10X	19.5	2830	21.5	3110	95
H335	21.0	2789	23.0	3033	88
♦ TAC	22.0	2874	24.0	3104	94
IMR 4895	22.0	2805	24.0	3018	106
