



22 Creedmoor Load Data

Case: Hornady

Barrel Length: 24"

Case Trim Length: 1.910"

Primer: Fed 210

Twist Rate: 1:7"

Bullet Weight	Bullet Type	Bullet SKU	Bullet S.D	Bullet G1 B.C	Cartridge O.A.L
55gr	TSX FB	30182	0.157	0.209	2.340"
55gr	TTSX BT	30187	0.157	0.272	2.414"
		Minimum		Maximum	
		Charge	Velocity	Charge	Velocity
		(grains)	(fps)	(grains)	(fps)
Powder					
IMR 7828SSC		42.8	3,464	47.1c	3,782
H4350		39.0	3,540	43.4	3,826
StaBall 6.5		39.7	3,464	44.1	3,864
RL 16		39.4	3,536	43.8c	3,877
Hunter		42.1	3,553	46.8c	3,879
Superformance		43.3	3,537	47.6	3,892



22 Creedmoor Load Data

Case: Hornady

Barrel Length: 24"

Case Trim Length: 1.910"

Primer: Fed 210

Twist Rate: 1:7"

Bullet Weight	Bullet Type	Bullet SKU	Bullet S.D	Bullet G1 B.C	Cartridge O.A.L
62gr	TSX BT	30156, 30190	0.177	0.296	2.405"
62gr	TTSX BT	30188	0.177	0.294	2.414"
		Minimum		Maximum	
		Charge	Velocity	Charge	Velocity
		(grains)	(fps)	(grains)	(fps)
Powder					
H4350		37.3	3,319	41.5	3,622
IMR 7828SSC		41.4	3,321	46.0c	3,663
StaBall 6.5		39.0	3,288	43.3	3,688
RL 26		41.8	3,386	46.4c	3,723
Hunter		41.5	3,409	46.1c	3,742
Superformance		42.7	3,399	47.4c	3,799



22 Creedmoor Load Data

Case: Hornady

Barrel Length: 24"

Case Trim Length: 1.910"

Primer: Fed 210

Twist Rate: 1:7"

Bullet Weight	Bullet Type	Bullet SKU	Bullet S.D	Bullet G1 B.C	Cartridge O.A.L
69gr	Match Burner	30162	0.196	0.339	2.470"
70gr	TSX BT	30158, 30193	0.199	0.323	2.460"
		Minimum		Maximum	
		Charge	Velocity	Charge	Velocity
Powder		(grains)	(fps)	(grains)	(fps)
N-560		40.8	3,157	45.4c	3,456
IMR 7828SSC		39.1	3,129	43.4	3,458
StaBall 6.5		37.7	3,127	41.9	3,487
Hunter		39.6	3,214	44.0	3,502
RL 26		40.1	3,243	44.1	3,523
Superformance		40.4	3,202	44.9	3,543



22 Creedmoor Load Data

Case: Hornady

Barrel Length: 24"

Case Trim Length: 1.910"

Primer: Fed 210

Twist Rate: 1:7"

Bullet Weight	Bullet Type	Bullet SKU	Bullet S.D	Bullet G1 B.C	Cartridge O.A.L
77gr	Match Burner	32050	0.219	0.352	2.470"
77gr	LRX BT	30881	0.219	0.404	2.560"

Powder	Minimum		Maximum	
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)
H4831	38.0	3,044	42.2	3,277
IMR 7828SSC	37.7	3,017	41.9	3,280
N-560	39.8	3,083	44.2	3,320
Magnum	43.3	2,984	48.1c	3,325
H1000	41.7	3,084	45.9c	3,326
StaBall HD	42.8	2,967	47.6c	3,335
StaBall 6.5	37.2	3,039	40.8	3,346
RL 19	38.4	3,080	42.6c	3,371
Superformance	38.9	3,070	43.3	3,383
RL 26	39.5	3,091	43.9	3,398