

Revised 3/2008



\*Recommend crimping case neck into cannelure groove.

♦ Indicates most accurate load

### **.348 Winchester**

|                                    |                                 |             |       |
|------------------------------------|---------------------------------|-------------|-------|
| <b>Bullet Weight:</b> 220 gr       | <b>Case Trim Length:</b> 2.245" | <b>S.D.</b> | 0.260 |
| <b>Bullet Style:</b> Original FNSP | <b>Primer:</b> WLR              | <b>B.C.</b> | 0.301 |
| <b>COAL:</b> 2.770"                | <b>Barrel Length:</b> 26"       |             |       |
| <b>Case:</b> W-W                   | <b>Twist Rate:</b> 1:12"        |             |       |

| Powder   | Minimum         |                | Maximum         |                |                  |
|----------|-----------------|----------------|-----------------|----------------|------------------|
|          | Charge (grains) | Velocity (fps) | Charge (grains) | Velocity (fps) | Load Density (%) |
| ♦ H380   | 49.0            | 2211           | 53.0            | 2392           | 78               |
| IMR 4350 | 54.0            | 2302           | 58.0            | 2473           | 93               |

|                                    |                                 |             |       |
|------------------------------------|---------------------------------|-------------|-------|
| <b>Bullet Weight:</b> 250 gr       | <b>Case Trim Length:</b> 2.245" | <b>S.D.</b> | 0.295 |
| <b>Bullet Style:</b> Original FNSP | <b>Primer:</b> WLR              | <b>B.C.</b> | 0.327 |
| <b>COAL:</b> 2.770"                | <b>Barrel Length:</b> 26"       |             |       |
| <b>Case:</b> W-W                   | <b>Twist Rate:</b> 1:12"        |             |       |

| Powder  | Minimum         |                | Maximum         |                |                  |
|---------|-----------------|----------------|-----------------|----------------|------------------|
|         | Charge (grains) | Velocity (fps) | Charge (grains) | Velocity (fps) | Load Density (%) |
| ♦ H4895 | 43.0            | 2020           | 47.0            | 2208           | 77               |
| H380    | 46.0            | 2123           | 50.0            | 2308           | 77               |